

CS-800LX

The CS-800LX is the single plug version of our popular CS-800 hoist relay control. Hoists running through 7 pin Socapex, 7 pin Litton Veam or 14 pin Cannon use the CS-800LX. This model has the same versatility and function as the CS-800. Eight chain motors can be run individually or in unison. Both power distribution and relay control for the hoists reside in the same compact unit.

The basic design runs 3 phase motors at 208V-220V. The 50 amp input provides adequate current to run eight 1hp motors. Each of the 4 circuit breakers protects 2 motors.

Manual hoist selection and running is accomplished using any of our Remote Manual Run Handsets. A typical package is shown with our P8-CS-SQ-AK25 remote with 25 ft remote cable hardwired into the handset.

STANDARD FEATURES:

- Runs up to 8 hoists
- 50amp Hubbell power input connector
- Litton, Veam or Socapex output connectors
- Input phase reversal
- Phase power indicators
- 50amp main emergency disconnect contactors
- Choice of chassis: 19" rack mountable or radial curved sides for standalone use
- Branch circuit breaker, 2 hoists per breaker
- Safety keyswitch for on/off and phase reversal input phase reversal
- Protective bar over circuit breakers
- Multi-pin connector to accept our standard remote cable

OPTIONAL FEATURES:

- Road case with casters and remote storage pocket (shown)
- Phase okay indicator light
- Out of phase alarm or lockout function
- Half couplers for truss attachment
- Modification to run single phase hoists up to 50 amps total current
- Phase selector switch in place of keyswitch

**THE REMOTE IS SOLD SEPARATELY.
SEE SECTION ON REMOTE RUN
HANDSETS FOR A FULL SELECTION**

CS REMOTE FEATURES:

- Square or slim shape
- Detachable cable or hardwired cable models offered
- Hardwired units have 25 ft cable with metal strain relief at each end for added strength
- Up/down toggles with indicator leds for each hoist
- Momentary run switch
- Emergency stop/ power on/off toggle

SPECIFICATIONS:

- Rack mountable chassis dimensions: 19.0 in. W x 15.75 in. H x 6.0 in. D
- Standalone chassis dimensions: 16.5 in. W x 15.75 in. H x 7.0 in. D
- Weight: 35 lbs.
- Electrical: 208-240 vac, 50 amps, 50-60 hz, 3 phase



Remote and case are sold separately.