

CS-400REC

The CS-400REC runs 4 motors at 380-416vac 3 phase using Cee connectors. Cee connectors for hoist hookup and power input are available in many configurations such as 4 pin or 3 pin control and 4 or 5 wire input.

Manual hoist selection and running is accomplished using any of our Remote Manual Run Handsets. A typical package is shown with our P4-CS-SQ-AK25 remote in our optional roadcase.



Remote and case are sold separately.

**ALSO AVAILABLE IN
SINGLE PHASE VOLTAGES**

**THE REMOTE IS SOLD SEPARATELY.
SEE SECTION ON REMOTE RUN
HANDSETS FOR A FULL SELECTION**

STANDARD FEATURES:

- Runs up to 4 hoists
- 16amp Cee form 380-416vac 3 phase input connector
- Cee form power and control output connectors
- 50amp main emergency disconnect contactors
- Safety keyswitch for on/off and phase selection
- Input phase reversal
- Phase power indicators
- Choice of chassis: 19" rack mountable or radial curved sides for standalone use
- Branch circuit breaker protection
- Multi-pin connector to accept our standard remote cable

OPTIONAL FEATURES:

- Road case with casters and remote storage pocket (shown)
- Phase okay indicator light
- Out of phase alarm or lockout function
- Half couplers for truss attachment
- Modification to run single phase hoists up to 32amps total current
- Modification to run hoists with Hubbell at 380-416vac
- CE marking
- Phase selector switch in place of keyswitch

CS REMOTE FEATURES:

- Detachable cable or hardwired cable models offered
- Hardwired units have 25 ft cable with metal strain relief at each end for added strength
- Up/down toggles with indicator leds for each hoist
- Momentary run switch
- Emergency stop/ power on/off toggle

SPECIFICATIONS:

- Rack mountable chassis dimensions:
49 cm W x 40 cm H x 16 cm D
- Standalone chassis dimensions:
42 cm W x 40 cm H x 18 cm D
- Weight: 16.33 kg.
- Electrical: 380-416 vac, 16 amps, 50-60 hz, 3 phase