



CBL-50A-CAM
(Power Feed Adapter Cable)



CBL-50A-BARE
(Power Feed Tail)



CBL-RX-TJ21K
(Remote Extension Cable)



CBL-XLR4
(Sensor Cable)



CBL-TJ19K
(Sensor Multi Cable)



CBL-HST-SX07



CBL-50A-50A
(Standard Power Feed Cable for CS-800)



CBL-RC-TJ21K
(Remote Cable)



CBL-HST-HBL
(Hoist power-control cable sets)



CBL-HST-HBL167

SINGLE LINE DUAL TWISTLOCK HOIST CABLES

Skjonberg Controls has redesigned the hoist cable. Users of dual twistlock hoists can now have the advantage of a single run cable.

Dual twistlock connectors on two 18 inch runs of 16AWG 4 conductor cable are spliced into one 16AWG 7 conductor SOOW cable. Each conductor is insulated to prevent shorting, then encased in molded santoprene rubber Y splitters.

A convenient snap hook strain is securley attached to the cable with plastic coated aircraft cable.

A wide range of Hubbell twistlock connectors are offered. Alternatively, the cables can be provided without connectors for end user retrofit.

Cables are offered at 100 ft anf 50 ft lengths. The 50 ft cable weighs just 16 lbs, fully assembled.